ATTORNEY DOCKET NO. 10847ABUS01U (NORT10-00170)
U.S. SERIAL NO. 09/475,269
PATENT

AMENDMENTS TO THE CLAIMS:

1. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising the steps of:

identifying a parameter associated with a data packet transported across the network; measuring the parameter; and

enabling optimization of the network bandwidth when said measured parameter differs from a predetermined value.

2. (Original) Apparatus for dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising:

first and second PBX cabinets interconnected in a local area network configuration for sending and receiving data packets;

a register in connection with at least one of said cabinets for storing a value associated with a given packet;

a comparator for comparing said value with a predetermined value; and

an optimization mechanism for adjusting the bandwidth of the network when said measured value differs from a predetermined value.

ATTORNEY DOCKET NO. 10847ABUS01U (NORT10-00170) U.S. SERIAL NO. 09/475,269 PATENT

3. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 1, wherein:

said parameter comprises a sequence number associated with the payload portion of said data packet.

4. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 1, wherein:

said parameter comprises measurement of the difference in arrival times of packets sent across the network and back between a first packet and a second packet.

5. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 1, wherein:

said parameter comprises measurement of the difference in arrival times of packets sent across the network and back between the average value of arrival times of a group of packets and a second packet.

6. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 3, further comprising the substep of: storing the sequence numbers of data packets in a register.

Page 3 of 15

D06

ATTORNEY DOCKET NO. 10847ABUS01U (NORT10-00170) U.S. SERIAL NO. 09/475,269 PATENT

- 7. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 6 further comprising the substep of: storing sequence numbers associated with successive data packets in the register.
- 8. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 7 further comprising the substep of:

 monitoring the sequence of sequence numbers associated with successive data packets stored.
- 9. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 8 further comprising the substep of:

incrementing a counter in the register by a count of one when the sequence numbers of successive data packets stored are in sequential order; and

incrementing the counter by a count greater than one when the sequence numbers of successive data packets stored are out of sequential order.

10. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 9, further comprising the substep of:

initiating bandwidth optimization when said counter count is incremented by a count greater than one.

007

- 11. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 10, wherein:

 said bandwidth optimization comprises static optimization.
- 12. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 11, wherein:

 said static optimization comprises limiting the number of channels available on the network.
- 13. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 10, wherein:

 said bandwidth optimization comprises adaptive optimization.
- 14. (Original) A method of dynamically adapting a PBX network to maintain a Quality of Service level in the network comprising as set forth in claim 13, wherein:

said adaptive optimization comprises the step of determining which channels are physically represented by cards connected to a PBX network cabinet.

10/19/05

ATTORNEY DOCKET No. 10847ABUS01U (NORT10-00170) U.S. SERIAL No. 09/475,269 PATENT

(Original) A method of dynamically adapting a PBX network to maintain a Quality of 15. Service level in the network comprising as set forth in claim 13, wherein:

said adaptive optimization comprises the step of determining whether a channel is inactive and re-mapping an active channel to an available inactive one.

16.-19. (Canceled)

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 20. Quality of Service level in the network comprising:

a parameter identifying mechanism for identifying a parameter associated with a data packet transported across the network;

a parameter measuring device for measuring the parameter; and

an optimization enabling device for optimizing the bandwidth of the network when said measured parameter differs from a predetermined value.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 21. Quality of Service level in the network as set forth in claim 20, wherein:

said parameter comprises a sequence number associated with the payload portion of said data packet.

*D*Ø9

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 22. Quality of Service level in the network as set forth in claim 20, wherein:

said parameter is derived from measurement of the difference in arrival times of packets set across the network and back between a first packet and a second packet.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain 23. Quality of Service level in the network as set forth in claim 20, wherein:

said parameter is derived from measurement of the difference in arrival times of packets sent across the network and back between the average value of arrival times of a group of packets and a second packet.

- (Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 24. Quality of Service level in a network as set forth in claim 21, wherein: sequence numbers of the data packets are stored in a register.
- (Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 25. Quality of Service level in a network as set forth in claim 24 wherein:

sequence numbers associated with successive data packets are stored in the register.

10/19/05

ATTORNEY DOCKET NO. 10847ABUS01U (NORT10-00170) U.S. SERIAL No. 09/475,269 **PATENT**

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 26. Quality of Service level in the network as set forth in claim 25 wherein:

the sequence of sequence numbers associated with stored successive data packets is monitored.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 27. Quality of Service level in the network comprising as set forth in claim 26 wherein:

a counter in the register is incremented by a count of one when the sequence numbers of successive data packets stored are in sequential order; and

the counter is incremented by a count greater than one when the sequence numbers of successive data packets stored are out of sequential order.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 28. Quality of Service level in the network as set forth in claim 27, wherein:

bandwidth optimization is initiated when the counter count is incremented by a count greater than one.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a **29**. Quality of Service level in the network as set forth in claim 28, wherein:

bandwidth optimization comprises static optimization.

Page 8 of 15

17:58

- (Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a **30**. Quality of Service level in the network as set forth in claim 29, wherein:
 - static optimization comprises limiting the number of channels available on the network.
- (Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 31. Quality of Service level in the network as set forth in claim 28, wherein:

bandwidth optimization comprises adaptive optimization.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 32. Quality of Service level in the network as set forth in claim 29, further comprising:

adaptive optimization apparatus which determines which channels are physically represented by cards connected to a PBX network cabinet.

(Previously Presented) Apparatus for dynamically adapting a PBX network to maintain a 33. Quality of Service level in the network comprising as set forth in claim 29, wherein:

adaptive optimization determines whether a channel is inactive and re-maps an active channel to an available inactive one.

34.-37. (Canceled)